



MISCELLANEOUS DEVICES

workaci.com | 1-888-967-5224



Automation Components, Inc.

2305 Pleasant View Road | Middleton, WI 53562



Applications:

Smoke Detectors:

- Data Centers
- Commercial Buildings
- Restaurants

Freeze Stats:

- Low Limit Temperature Protection for HVAC Equipment

Light Level Sensors:

- Outdoor/Security Lighting

Leak Detection:

- AHU Drip Pans
- Floor Drains
- Contained Spaces

Power Supplies/Relays

Mounting Hardware & Accessories

MISCELLANEOUS DEVICES

ACI offers additional products such as freeze stats, smoke detectors, power supplies, light level sensors, leak detectors, mounting clips/brackets, and others. Please contact us for technical and application support.


RT-3000 SMOKE DETECTOR

The RT-3000 is UL listed and easy to install. It features a tool-less NEMA 4X enclosure and easily replaceable detector heads. The trimmable FAST TUBE sampling tubes allow for the RT-3000 to cover a wide variety of installations.



SM-501 & SL-2000 [ROUND DUCTS] SMOKE DETECTOR

The SM-501 and SL-2000 smoke detectors are low-cost solutions for early smoke detection in commercial, industrial, or residential applications. They are easy to install and have replaceable heads.



MS SERIES [REMOTE ACCESSORIES FOR SMOKE DETECTORS]

The MS series remote accessories are designed to be used with ACI duct smoke detectors to provide audible and visual indications and remote test/reset functions. These devices are constructed of attractive yet durable brushed stainless steel and are mounted on a standard single or double gang electrical box.



MSR-50 SERIES [REMOTE ACCESSORIES FOR SMOKE DETECTORS]

The MSR-50R series remote accessories are designed for use with ACI duct smoke detectors to allow for remote test and reset functions typically required by building inspectors for commercial applications.



FLS SERIES FREEZE STATS

The FLS series low limit thermostats (freeze stats) use a vapor-filled capillary to alert when equipment is in danger of freezing. This series is UL listed, has a rugged metal housing, auto or manual reset, two relay contacts, and is available in lengths of up to 50'. Capillary mounting clips are also available.




FS SERIES FREEZE STATS

The FS series freeze stats are a low-cost and reliable low limit thermostat. Options include one or two relay contacts, auto or manual reset, and lengths up to 50'. Capillary mounting clips are also available.



PS24 POWER SUPPLY

The PS24 low voltage power supply accepts a 24 VAC input and converts it to an adjustable 1.5—26 VDC output. The PS24 can be configured either half- or full-wave rectification by using the on-board jumpers.



LIGHT LEVEL

The A/LLS and A/LLS-T light level sensors and transmitters are used for controlling indoor or outdoor lighting. The sensor can be mounted in a NEMA 3R enclosure. In darkness, the sensor has a resistance in excess of 1M ohms versus a resistance of less than 1.5K ohms in bright light.



PAM RELAYS

PAM relays are low cost, small, and easy to install. These SPDT relays are available in numerous voltage and contact rating options.



LEAK DETECTION

ACI leak detectors range from small and simple spot leak detectors to complete systems with communicating controllers.





WE HAVE YOU COVERED!



From engineering and design services to installation and troubleshooting, our Technical Support Team offers expert support for every customer and every application. Our Sales and Customer Support Teams can help with quotes, order status, invoicing, and many product spec and application questions.

CONTACT US

Phone: 1-888-WORKACI (967-5224)

Live Chat: Click the Chat button on every page of our website: workaci.com

Tech Support Email: techsupport@workaci.com

Customer Support Email: orders@workaci.com

Hours: 7:00 a.m. to 5:30 p.m. Central, Monday – Friday



STAY CONNECTED

workaci.com | 1-888-967-5224 | 2305 Pleasant View Rd., Middleton, WI